

COMMODORE® AMIGA® 2065

10Mbps Ethernet
Local Area Network (LAN) Board

Supports both Type A (Thick
Ethernet) and Type B (Thin
Ethernet/CheaperNet) Connections

Full support for Amiga
AUTOCONFIG™

Multiple A2065 Boards may
be used simultaneously



ETHERNET NETWORK INTERFACE ADAPTER

COMMODORE® AMIGA® 2065

FUNCTION

Provides full ANSI 802.3 type Ethernet protocols over either Type A (Thick Ethernet) or Type B (Thin Ethernet/Cheapernet) connections
32K onboard RAM Buffer provides shared RAM between Am7990 processor and the Amiga computer

CARD TYPE

Amiga bus (100 pin)
Full support for Amiga AUTOCONFIG™

INTERFACE SPECS

15 pin female "D" connector for Type A (Thick Ethernet) networking with 100 nodes per segment
Female BNC coax connector for Type B (Thin Ethernet/Cheapernet) networking with 30 nodes per segment

SPEED

10Mbps CSMA/CD interface
DMA data reading and writing to shared RAM

CARD SIZE

Full size Amiga board

POWER REQUIREMENTS

Supplied by Amiga Computer

ETHERNET NETWORK INTERFACE ADAPTER



1200 Wilson Drive
West Chester, PA 19380

Commodore and the Commodore logo are registered trademarks of Commodore Electronics Limited
Amiga is a registered trademark of Commodore-Amiga, Inc.
AUTOCONFIG is a trademark of Commodore Electronics Limited

Specifications are subject to change without notice

A2065-SS-0291